

ISTA 1 Series  
Non-  
Simulation  
Integrity  
Performance  
Test  
Procedure

VERSION  
DATE  
Last  
TECHNICAL  
Change:  
MARCH  
2014  
  
Last  
EDITORIAL  
Change:  
JANUARY  
2012

For complete  
listing of  
Procedure  
Changes and  
Version Dates  
go to  
[www.ista.org](http://www.ista.org)

Preface

## ISTA, Distributing Confidence, Worldwide™

ISTA 1 Series are the most basic category of performance tests.

- They challenge the capability of the package and product to withstand transport hazards, but
- They are not simulations of actual transport hazards, and
- Do not necessarily comply with carrier packaging regulations.

When properly applied, ISTA procedures will provide tangible benefits of:

- Shortened packaged development time and confidence in product launch
- Protection of products and profits with reduced damage and product loss
- Economically balanced distribution costs
- Customer satisfaction and continued business.

There are three sections: Overview, Testing and Report

- Overview provides the general knowledge required before going into the testing laboratory and
- Testing presents the specific instructions to do the testing in the laboratory and
- Report indicates what data shall be recorded to submit a test report to ISTA.

Two systems of weights and measures are presented in ISTA test procedures. They are the English system (Inch-Pound) and the international system SI (Metric). Inch-Pound units are shown first with Metric units in brackets, except in some tables where they are shown separately.

- Either system may be used as the unit of measure (standard units), but
- The standard units chosen shall be used consistently throughout the procedure.
- Units are converted to two significant figures and
- Not exact equivalents.

### **VERY IMPORTANT:**

**The entire document shall be read and understood before proceeding with a test.**

## OVERVIEW OF PROCEDURE 1A

Test Procedure 1A is an integrity test for individual packaged-products.

- It can be used to evaluate the performance of a packaged-product.
- It can be used to compare relative performance of package and product design alternatives.
- The package and product are considered together and not separately.
- Some conditions of transit, such as moisture, pressure or unusual handling, may not be covered.

Other ISTA Procedures may be appropriate for different conditions or to meet different objectives.

Specific suggestions:

- To use random vibration instead of fixed displacement vibration, use ISTA Test Procedure 1G and not 1A.
- For packaged-products where a minimum compression value should be tested, use ISTA Test Procedure 1C.
- For packaged-products intended for international distribution consider ISTA Partial-Simulation Performance Test Procedure 2A.
- For packaged-products that may be transported in a small parcel delivery system consider ISTA General Simulation Performance Test Procedure 3A.

Refer to *Guidelines for Selecting and Using ISTA Procedures and Projects* for additional information.

## Scope

Test Procedure 1A covers testing of individual packaged-products weighing 150 lb (68 kg) or less when prepared for shipment.

**EXCEPTION:**

Individual packaged-products on a visible skid or pallet and that weigh more than 100 lb (45 kg) may be tested according to Test Procedure 1B or 1E.

Product  
Damage  
Tolerance and  
Package  
Degradation  
Allowance

The shipper shall determine the following prior to testing:

- what constitutes damage to the product and
- what damage tolerance level is allowable, if any, and
- the correct methodology to determine product condition at the conclusion of the test and
- the acceptable package condition at the conclusion of the test.

For additional information on this determination process refer to *Guidelines for Selecting and Using ISTA Procedures and Projects*.

## Samples

Samples should be the untested actual package and product, but if one or both are not available, the substitutes shall be as identical as possible to actual items.

Number of samples required:

- One sample is required for the tests in this procedure.

Replicate Testing Recommended:

To permit an adequate determination of representative performance of the packaged-product, ISTA:

- Requires the procedure to be performed one time, but
- Recommends performing the procedure five or more times using new samples with each test.

**NOTE:**

Packages that have already been subjected to the rigors of transportation cannot be assumed to represent standard conditions. In order to insure testing in perfect condition, products and packages shipped to certified laboratories for testing must be:

- over-packaged for shipment to the laboratory or
- repackaged in new packaging at the laboratory.

Test  
Sequence

The tests shall be performed on each test sample in the sequence indicated in the following table:

Sequence #	Test Category	Test Type	Test Level	For ISTA Certification
1	Atmospheric Preconditioning	Temperature and Humidity	Ambient	Required
2	Vibration	Fixed Displacement	1 in (25mm) peak-to-peak at a frequency to be determined	Required
3	Shock (Alternative methods allowed – select one test type)	Drop	Height varies with packaged-product weight	Required
		Incline-Impact (Conbur)	Impact Velocity varies with packaged-product weight	
		Horizontal Impact	Impact Velocity varies with packaged-product weight	





Equipment  
Required  
Vibration

## Fixed Displacement Vibration Test:

- Vibration Test System with a 1 in (25 mm) fixed or controlled displacement complying with Method A1 or A2 of the apparatus section of ASTM D 999.  
Rotary or vertical linear motion of the platform is acceptable.
- Metal shim 0.06 in (1.5 mm), thick approximately 2 in (50 mm) wide and at a convenient length.
- Tachometer or suitable indicator for determining vibration frequency in cycles per second (Hz) or cycles per minute (CPM).
- Automatic timer or stopwatch.

Equipment  
Required  
Shock

The following alternatives are acceptable for the equipment required for the Shock Test:

Type of Shock Test	Type of Equipment	In compliance with the apparatus section of ...
Drop Test	Free fall drop tester 	ASTM D 5276
Vertical Shock Test	Shock test machine 	ASTM D 5487
Alternative Incline Test	Incline impact tester (conbur) 	ASTM D 880
Alternative Horizontal Test	Horizontal impact test system 	ASTM D 4003

Prior to beginning the tests identify the faces, edges and corners according to the procedure below.

Step	Action
1	Place the packaged-product in its intended shipping position as determined by shipper. If the shipping position can be variable, place the packaged-product so that the primary shipping label location is on the top face.
2	Does the packaged-product have only six faces (2 sides, 2 ends, top and bottom)? <ul style="list-style-type: none"> <li>If Yes, then go to Step 5.</li> <li>If No, continue to next Step.</li> </ul>
3	Develop a method to identify each face, edge and corner and document with a diagram.
4	Go to next page for further Before You Begin details.
5	Is the package a corrugated container? <ul style="list-style-type: none"> <li>If Yes, continue to next Step.</li> <li>If No, then go to Step 8.</li> </ul>
6	Does the package have a manufacturer's joint connecting a side and an end face? <ul style="list-style-type: none"> <li>If Yes, continue to next Step.</li> <li>If No, then go to Step 8.</li> </ul>
7	Turn the packaged-product so that you are looking directly at a face with the manufacturer's joint on the observer's right and go to Step 9.
8	Position one of the smallest width faces of the packaged-product directly in front of you.
9	Identify faces according to the diagram below. <div data-bbox="560 1020 1440 1543"> </div>
10	Identify edges using the numbers of the two faces forming that edge. Example: Edge 1-2 is the edge formed by face 1 and face 2 of the packaged-product.
11	Identify corners using the numbers of the three faces that meet to form that corner. Example: Corner 2-3-5 is the corner formed by face 2, face 3, and face 5 of the packaged-product.
12	Go to next page for further Before You Begin details.

Weight and  
Size  
Measurement

Before You  
Begin  
Atmospheric  
Conditioning  
O

Before You  
Begin  
Vibration  
Testing

You shall know the packaged-product's:

- gross weight in pounds (kg), and
- outside dimensions of Length, Width and Height (L x W x H) in inches (mm or m)

#### Required Preconditioning:

The packaged-product shall be preconditioned to laboratory ambient temperature and humidity for twelve (12) hours prior to testing.

#### CAUTION:

A restraining device or devices shall be used with the vibration test system to:

- Prevent the test specimen from moving off the platform and
- Maintain test orientation of the packaged-product, but
- The device or devices shall not restrict the vertical motion of the test specimen during the test.

Familiarity with the following formula is required to calculate the test duration after the frequency required to bounce the packaged-product is determined in the Vibration Test Block:

$$\text{Test Duration in Minutes} = \frac{14,200 \text{ Vibratory Impacts}}{\text{Cycles Per Minute (CPM) or [Cycles Per Second (Hz) x 60]}}$$

The chart below shows example Test Durations calculated for several frequencies.

CPM	Hz	Test Duration in Minutes
150	2.5	95
180	3.0	79
210	3.5	68
240	4.0	60
270	4.5	53
300	5.0	48

Before You  
Begin  
Shock Testing

The test drop height varies with the weight of the packaged-product. Find the weight of the packaged-product in the following chart to determine a drop height or an equivalent impact velocity or velocity change to be used for a substituted drop:

Packaged-Product Weight				Drop Height			Impact Velocity	
Equal to or greater than		But Less than		Free Fall			Incline or Horizontal	
lb	kg	lb	kg	in.	mm		ft/s	m/s
0	0	21	10	30	760		13	3.9
21	10	41	19	24	610		11	3.5
41	19	61	28	18	460		10	3.0
61	28	100	45	12	310		8.0	2.5
100	45	150	68	8	200		6.6	2.0

- The test method requires the packaged-product to be dropped in several different package orientations.
- A drop test must be performed in all required orientations where dropping the packaged-product is practical.
- If dropping in a required orientation is not practical an equivalent incline or horizontal test can be substituted for that orientation.
- When using impact velocity or velocity change, if any velocity in a Test Sequence is below the required minimum level, that sequence event must be repeated until the test velocity meets the minimum.

TEST BLOCK 1  
Atmospheric  
Conditioning  
O

The test blocks that follow contain tables that indicate the required steps for each test in the procedure.

TEMPERATURE AND HUMIDITY	
Step	Action
1	PRE-CONDITIONING: The packaged-product should be stored at laboratory ambient temperature and humidity for twelve (12) hours prior to testing.
2	Record the ambient laboratory temperature and humidity when testing starts.
3	At the end of testing record temperature and humidity.
4	Go to TEST BLOCK 2 (Vibration).

TEST BLOCK 2  
Vibration

VIBRATION –FIXED DISPLACEMENT	
Step	Action
1	Put the packaged-product on the vibration table so that face 3 rests on the platform.
2	Start the vibration system to vibrate at 1.0 in (25 mm) total displacement at the machine's lowest frequency.
3	Maintain a fixed displacement at 1 inch (25 mm) and slowly increase the frequency (speed) of the vibration table until the packaged-product begins to momentarily leave the surface of the platform.
4	Can a metal shim be intermittently moved between the bottom of the longest dimension of the packaged-product and the surface of the platform? <ul style="list-style-type: none"> <li>If Yes, hold that frequency and then continue to the next Step (Step 5).</li> <li>If No, then slowly increase the frequency until the requirement of this Step (Step 4) is met, and hold that vibration frequency.</li> </ul>
5	Determine the test duration in minutes using the formula indicated in Before You Begin Vibration Testing and the CPM or Hz frequency identified in Step 4.
6	Begin timing the vibration test duration.
7	Are you using a vertical linear motion on the vibration system? <ul style="list-style-type: none"> <li>If Yes, then go to Step 12.</li> <li>If No, then continue with the next Step.</li> </ul>
8	Stop the vibration test after completion of one-half ( $\frac{1}{2}$ ) of the total minutes of test duration and perform the appropriate action as indicated in the table below:
	IF a single 90° horizontal rotation is...
	Possible
	Not practical because of the size of the packaged-product or the stability of the packaged-product.
THEN perform a horizontal rotation of ...	
90° as the specimen rests on the platform.	
180° as the specimen rests on the platform.	
9	Re-start the vibration system to vibrate at 1.0 in (25 mm) total displacement at the machine's lowest frequency.
10	Maintain a fixed displacement at 1 inch (25 mm) and slowly increase the frequency (speed) of the vibration table until the packaged-product begins to momentarily leave the surface of the platform.
11	Can a metal shim be intermittently moved between the bottom of the longest dimension of the packaged-product and the surface of the platform? <ul style="list-style-type: none"> <li>If Yes, hold that frequency and then continue to the next Step (Step 12).</li> <li>If No, then slowly increase the frequency until the requirement of this Step (Step 11) is met, and hold that vibration frequency.</li> </ul>
12	Resume or continue timing the test, and complete the second half of the vibration duration.
13	Vibration testing is now complete. Go to TEST BLOCK 2 (Shock).

TEST BLOCK3  
Shock

SHOCK - DROP			
Step	Action		
1	Determine the method(s) of test and the required drop height or impact velocity in Before You Begin Shock Testing.		
2	Do you have a packaged-product with only 6 faces as identified in Face, Edge and Corner Identification? <ul style="list-style-type: none"> <li>If Yes, continue with the next Step.</li> <li>If No, then go to Step 6.</li> </ul>		
3	Test the packaged-product according to the method(s) and level(s) determined in Step 1. Follow the sequence in the table below.		
4	<b>Sequence #</b>	<b>Orientation</b>	<b>Specific face, edge or corner</b>
	1	Corner	most fragile face-3 corner, if not known, test 2-3-5
	2	Edge	shortest edge radiating from the corner tested
	3	Edge	next longest edge radiating from the corner tested
	4	Edge	longest edge radiating from the corner tested
	5	Face	one of the smallest faces
	6	Face	opposite small face
	7	Face	one of the medium faces
	8	Face	opposite medium face
	9	Face	one of the largest faces
	10	Face	opposite large face
5	All testing is now complete. Go to the Reporting an ISTA Test section at the end of this Procedure.		
6	Select a bottom face corner to replace the corner required in Step 4 Sequence 1 to begin the test.		
7	Identify the edges of the packaged-product that meet the Step 4 Sequence 2 through 4 requirements.		
8	Select any 6 faces to replace the faces required in Step 4 Sequence 5 through 10.		
9	Using the corner, edges and faces from Steps 6 through 8 go to Step 3 and proceed.		
10	All testing is now complete. Go to the Reporting an ISTA Test section at the end of this Procedure.		

ISTA Test Report Forms may be downloaded by members through the online ISTA Member Center ([www.ista.org/members/](http://www.ista.org/members/)). Custom forms are also acceptable, but information on an official ISTA Report Form is considered to be the minimum required for any test report submission and consideration. Test report forms should be submitted to ISTA Headquarters by mail, fax or electronically. Test reports should be detailed enough for accurate repeatability of the test.

The packaged-product has satisfactorily passed the test if, upon examination, it meets the Product Damage Tolerance and Package Degradation Allowance determined prior to testing.

ISTA Certified Testing Laboratories:

- Should file a test report on all ISTA Test Procedures or Projects conducted.
- Shall file a test report on all ISTA Test Procedures or Projects conducted to obtain Transit Tested Package Certification or Acknowledgement.

To submit a test report form:

- Email to [ista@ista.org](mailto:ista@ista.org)
- Mail to address shown below
- Fax to +1 517-333-3813.

#### ISTA Transit Tested Program: Packaged-Product Certification

The ISTA Transit Tested Certification Mark as shown:

- is a registered certification mark and
- can only be printed on certified packages and
- can only be used by license agreement and
- by a Shipper member of the International Safe Transit Association.



When a Shipper member prints this certification mark on a packaged-product, with their manufacturer's license number, they are showing their customer, vendors and carriers that it has passed the requirements of ISTA preshipment testing.

To obtain initial certification of a packaged-product:

- the product manufacturer must be a Shipper member of ISTA in good-standing and with a valid License Agreement on file
- the testing laboratory must be a member of ISTA in good-standing and have a valid lab certification date
- a test report must be submitted by the laboratory to ISTA Headquarters.

In order to maintain its certified status and eligibility for identification with the Transit Tested Certification Mark, each packaged-product must be re-tested whenever a change is made in the:

- Product or
- Process or
- Package.

If corrugated packaging is used, it is recommended that the basis weights of the constituent papers/paperboards be determined after testing and documented to provide the best indicator of equivalence or change.

As a quality control procedure, packaged-products should be re-tested frequently, for example, yearly.

For additional information, refer to *Guidelines for Selecting and Using ISTA Test Procedures and Projects*.

ISTA Membership information is available at [www.ista.org](http://www.ista.org).

*This Test Procedure is published by:*

*International Safe Transit Association*

*1400 Abbot Road, Suite 160, East Lansing, Michigan 48823-1900 USA*

© 2014 International Safe Transit Association

*No part of the contents of this Test Procedure may be reproduced or transmitted in any form or by any means without the written permission of the publisher.*

Order Information: Additional copies of this Test Procedure and the ISTA® RESOURCE BOOK may be ordered online at [www.ista.org](http://www.ista.org) or by contacting ISTA at (+1) 517.333.3437. A listing of current procedure version dates is available at [www.ista.org](http://www.ista.org).